

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product

R 507

Art-Nr(n): 0055

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Remark

Restricted to professional users.

Recommended intended purpose(s)

Refrigerant.

1.3. Details of the supplier of the safety data sheet

Manufacturer/distributor

S. Zukausko str. 11, Ramuciai, Kaunas district,

LT - 54464, Lithuania

Phone + 370 37 373248

Fax. + 370 37 373198

E-mail: info@brgroup.eu

www.brgroup.eu

1.4. Emergency telephone number

Emergency advice

The Poison Information Bureau

Siltnamij str. 29, LT-2043 Vilnius

Phone +370 5 2362052;

Fax. +370 5 236 21 42,

E-mail.: info@tox.lt

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard
categories

Hazard Statements Classification procedure

Liquef. Gas

H280

Hazard statements for physical hazards

H280 Contains gas under pressure; may explode if heated.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS04

Signal word

Warning

Hazard statements for physical hazards

H280 Contains gas under pressure; may explode if heated.

Precautionary Statements**Storage**

P403 Store in a well-ventilated place.

Hazardous ingredients for labeling

1,1,1-Trifluoroethane (R 143a), Pentafluoroethane (R 125)

Supplemental Hazard information (EU)**Environmental properties**

Contains fluorinated greenhouse gases.

Special rules for supplemental label elements for certain mixtures

Withdrawal out of the liquid phase only.

2.3. Other hazards**Adverse human health effects and symptoms**

Contact with liquid may cause cold burns/frostbite.

Asphyxiant in high concentrations.

The inhalation of gas / vapour in high concentrations may cause cardiac arrhythmia.

Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Information pertaining to special dangers for human and environment

Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

Receptacle under pressure.

Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

SECTION 3: Composition/ information on ingredients**3.1. Substances**

not applicable

3.2. Mixtures

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
354-33-6	206-557-8	Pentafluoroethane (R 125)	50	Liq. Gas, H280
420-46-2	206-996-5	1,1,1-Trifluoroethane (R 143a)	50	Liq. Gas, H280 / Flam. Gas 1, H220

REACH

CAS No	Name	REACH registration number
354-33-6	Pentafluoroethane (R 125)	01-2119485636-25
420-46-2	1,1,1-Trifluoroethane (R 143a)	01-2119492869-13

Additional advice

The text of the H-and EUH-phrases is shown in section 16.

Contains fluorinated greenhouse gases.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

Adhere to personal protective measures when giving first aid.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

Seek medical treatment immediately.

In case of respiratory standstill give artificial respiration by respiratory bag (Ambu bag) or respirator. Send for a doctor.

In case of skin contact

In case of contact with skin wash off with warm water.

In case of frostbite rinse with plenty of water. Don't remove clothing.

In case of frostbite spray with lukewarm (not hot) water for at least 15 minutes. Do not remove clothing frozen to the skin. Thaw it with lukewarm water. Apply a sterile dressing. Obtain medical assistance.

In case of eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call for a doctor immediately.

In case of ingestion

Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

Physician's information / possible symptoms

The following symptoms may occur in case of strong exposition:

Unconsciousness

Cardiac arrhythmia (disordered cardiac rhythm).

Headache

Nausea

Confusion

Dizziness

Contact with liquid may cause cold burns/frostbite.

Physician's information / possible dangers

Long-term inhaling of separation products may cause pulmonary oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment (Advice to doctor)

Treat symptoms.

Do not give any preparations of the adrenalin-ephedrine group.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Product does not burn, fire-extinguishing activities according to surrounding.

Alcohol-resistant foam

Dry powder

Carbon dioxide

Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Formation of explosive gas mixtures in air.

Carbon monoxide (CO)

Carbon dioxide (CO₂)

Hydrogen fluoride (HF)

Carbonyl fluoride.

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply (isolated).

Wear full protective clothing.

Additional information

Cool endangered containers with water spray jet.

Exposure to fire may cause containers to rupture / explode.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Evacuate area.

Keep people away and stay on the upwind side.

For emergency responders

Remove persons to safety.

Personal protection by wearing close-fitting protective clothing and breathing apparatus.

Pay attention to extension of gas especially at ground (heavier than air) and in direction of the wind.

6.2. Environmental precautions

If possible, stop flow of product.

Do not discharge into the drains/surface waters/groundwater.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

If necessary, secure leaky pressure receptacles in a salvage packaging.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Ensure adequate air ventilation.

Allow to vaporise.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in thoroughly ventilated areas.

Transfer and handle only in enclosed systems.

Containers' temperature may not be increased above 50 °C.

Do not heat with open flames.

The working pressure in the receptacle must not exceed the saturation vapour pressure of the pure product resulting at a temperature of 50 °C.

Provide good room ventilation even at ground level (vapours are heavier than air).

Prevent cylinders from falling over.

Avoid release to the environment.

Ensure valve protection device is correctly fitted.

Ensure valve outlet cap nut or plug (where provided) is correctly fitted.

Open valve slowly to avoid pressure shock.

Do not allow backfeed into the container.

Suck back of water into the container must be prevented.

No water to valves, flanges and other fittings.

Purging of pipes and valves with inert gases - to avoid: water, solvents.

General protective measures

Do not inhale gases.

Hygiene measures

At work do not eat, drink and smoke.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

The product is not flammable in air under ambient conditions of temperature and pressure. When pressurised with air, oxygen or other oxidants, it may become flammable.

Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

Only use containers that are approved specifically for the substance/product.

Suitable materials: Normalised carbon steel, tempered alloy steel, aluminium alloys, austenitic stainless steels.

Valve: Suitable materials: Brass, copper alloys, carbon steels, aluminium alloys, austenitic stainless steels.

Other material details see ISO 11114.

All regulations and local requirements for the storage of containers have to be respected.

Advice on storage compatibility

Do not store together with spontaneously flammable materials.

Do not store together with combustible liquids or combustible solids.

Do not store together with animal feedstuffs.

Do not store together with explosives.

Do not store together with infectious substances.

Do not store together with radioactive material.

Do not store together with toxic liquids or toxic solids.

Do not store together with food.

Do not store together with oxidizing liquids or oxidizing solids.

Further information on storage conditions

Ensure valve protection device is correctly fitted.

Store only in original container at temperature of 50°C maximum (=122°F).

Protect from heat and direct solar radiation.

Prevent cylinders from falling over.

Keep container in a well-ventilated place

7.3. Specific end use(s)**Recommendation(s) for intended use**

Use in accordance with regulation (EU) No 517/2014 on fluorinated greenhouse gases.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****DNEL-/PNEC-values****DNEL worker**

CAS No	Substance name	Value	Code	Remark
354-33-6	Pentafluoroethane (R 125)	16444 mg/m3	DNEL long-term inhalative (systemic)	Assessment factor 7,5
420-46-2	1,1,1-Trifluoroethane (R 143a)	38800 mg/m3	DNEL long-term inhalative (systemic)	Assessment factor 3

DNEL Consumer

CAS No	Substance name	Value	Code	Remark
354-33-6	Pentafluoroethane (R 125)	1753 mg/m3	DNEL long-term inhalative (systemic)	Assessment factor 25
420-46-2	1,1,1-Trifluoroethane (R 143a)	10700 mg/m3	DNEL long-term inhalative (systemic)	Assessment factor 5

PNEC

CAS No	Substance name	Value	Code	Remark
354-33-6	Pentafluoroethane (R 125)	0,1 mg/l	PNEC aquatic, freshwater	Assessment factor 1000, Extrapolation
		0,6 mg/kg dw	PNEC sediment, freshwater	Extrapolation
		1 mg/l	PNEC aquatic, intermittent release	Assessment factor 100, Extrapolation
420-46-2	1,1,1-Trifluoroethane (R 143a)	0,35 mg/l	PNEC aquatic, freshwater	Assessment factor 1000

8.2. Exposure controls**Respiratory protection**

Breathing apparatus in the event of high concentrations.

Keep self contained breathing apparatus readily available for emergency use.

Do not use any filter apparatus.

Respiratory protection complying with EN 137.

In case of rescue and maintenance activities in storage containers use environment-independent breathing apparatus because of risk of suffocation by edging out of air oxygen

Hand protection

Leather gloves

Safety gloves according EN 388

Eye protection

Protective goggles according to EN 166, in case of increased risk add protective face shield.

Other protection measures

Safety shoes with steel toe.

Body covering work clothing, or chemical resistant suit at increased risk.

Appropriate engineering controls

Transfer and handle only in enclosed systems.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance**

Gaseous / liquefied under pressure.

Colour

colourless

Odour

ethereal

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not applicable				
boiling point	-46,7 °C		1013 hPa		
melting range	-111 - -103 °C				Data refer to the components of the mixture.
Flash point	not applicable				
Vapourisation rate	> 1				CCI4=1
Flammable (solid)	not applicable				
Flammability (gas)	no				EN 378-1
Ignition temperature	not determined				
Self ignition temperature	750 °C				R-143a
Lower explosion limit	no			ASTM E-681	
Upper explosion limit	no			ASTM E-681	
Vapour pressure	12826 hPa	25 °C			
Relative density	68,9 kg/m ³	25 °C			
Vapour density	3,5	25 °C			air = 1
Solubility in water	0,76 - 3,89 g/l	25 °C			Data refer to the components of the mixture.
Solubility/other	not determined				

	Value	Temperature	at	Method	Remark
Partition coefficient n-octanol/water (log P O/W)	1,48 - 1,73	20 - 25 °C			Data refer to the components of the mixture.
Decomposition temperature	not determined				
Viscosity	not applicable				

Oxidising properties

no

Explosive properties

no

9.2. Other information

Vapours are heavier than air.

SECTION 10: Stability and reactivity**10.1. Reactivity**

See section "Possibility of hazardous reactions".

10.2. Chemical stability

Stable under recommended conditions of use and storage (see section 7).

10.3. Possibility of hazardous reactions

May react violently with oxidants.

When pressurised with air, oxygen or other oxidants, the mixture may become flammable.

Reactions with alkali metals.

Reactions with earth alkali metals.

Reactions with metals in powder form.

Reactions with metal salts in powder form.

Reactions with strong alkalies.

10.4. Conditions to avoid

Heat sources / heat - risk of bursting.

Avoid contact with open flames, glowing metal surfaces, etc..

10.5. Incompatible materials**Substances to avoid**

Alkali (lye), concentrated

Metals in powder form.

Metallic salts in powder form.

Oxidants.

Alkali metals.

Earth alkali metals.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Fluorophosgene on contact open flame or glowing objects

Hydrogen fluoride

Fluorine
Carbonyl fluoride

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	Study technically not feasible.			
LD50 acute dermal	Study technically not feasible.			
LC50 acute inhalation	> 591000 ppm (4 h)	rat (male / female)	OECD 403	
Skin irritation	Study technically not feasible.			
Eye irritation	Study technically not feasible.			
Skin sensitization	Study technically not feasible.			
Sensitization respiratory system	non-sensitizing			

Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
Subchronic Toxicity	NOAEL > 40000 ppm (90 d) Inhalation 6 h/d, 5 d/w	Rat (male / female)	OECD 413	No effects of toxicological significance.
Mutagenicity				No experimental information on genotoxicity in vitro and in vivo available.
Reproduction-Toxicity			OECD 414	No indications of toxic effects were observed in reproduction studies in animals.
	The product has not been tested. The information is derived from products of similar composition.			

	Value	Species	Method	Validation
Carcinogenicity	NOAEL 300 mg/kg (1 a)	Rat		No indications of carcinogenic effects are available from long-term trials.
	Oral. R-143a			

Specific target organ toxicity (single exposure)

Substance or mixture is not classified in GHS-criteria as specific target organ toxic with single exposure.

Specific target organ toxicity (repeated exposure)

Substance or mixture is not classified in GHS-criteria as specific target organ toxic with repeated exposure.

Aspiration hazard

not applicable

Experiences made from practice

Inhalation causes disordered cardiac rhythm.

Inhalation causes shortness of breath.

Gases have a suffocating effect.

Inhalation causes narcotic effect/intoxication.

Additional information

The product has not been tested. The information is derived from the properties of the individual components.

SECTION 12: Ecological information**12.1. Toxicity****Ecotoxicological effects**

	Value	Species	Method	Validation
Fish	LC50 > 40 mg/l (96 h)	Oncorhynchus mykiss	OECD 203	
Daphnia	EC50 > 100 mg/l (48 h)	Daphnia magna	OECD 202	
Algae	EC50 > 71 mg/l (96 h)	Chlorobionta	QSAR	

12.2. Persistence and degradability

	Elimination rate	Method of analysis	Method	Validation
Physico-chemical degradability	At normal temperature very highly volatile or gaseous product that can be released to atmosphere. Elimination test cannot be employed.			
Biological degradability	< 5 % (28 d)		OECD 301 D	not readily degradable

12.3. Bioaccumulative potential

No high bioaccumulation potential.

Because of the n-octanol/water distribution coefficient (log K_{ow}) accumulation in organisms is not expected.

12.4. Mobility in soil

Because of its high volatility, it is unlikely that the product soil, water caused.

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6. Other adverse effects

ODP: 0

GWP: 3985

General regulation

The product has not been tested. The data are derived from the individual components of the mixture.

Avoid release to the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Waste code No.**

14 06 01*

Name of waste

chlorofluorocarbons, HCFC, HFC

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Dispose of as hazardous waste.

Return to manufacturer.

Recommendations for packaging

Transportable pressure equipment (empty, residual pressure): Return to supplier / manufacturer.

General information

Operators of stationary equipment shall be responsible for putting in place arrangements for the proper recovery.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	3163	3163	3163
14.2. UN proper shipping name	REFRIGERANT GAS, N.O. S. (Pentafluorethan (R 125), 1,1,1-Trifluorethan (R 143a))	REFRIGERANT GAS, N.O.S. (Pentafluorethan (R 125), 1,1, 1-Trifluoroethane (R 143a))	Refrigerant gas, n.o.s. (Pentafluorethan (R 125), 1,1,1-Trifluoroethane (R143a))
14.3. Transport hazard class(es)	2.2	2.2	2.2
14.4. Packing group	-	-	-
14.5. Environmental hazards	No	No	No

14.6. Special precautions for user

The protective measures listed in Sections 6, 7 and 8 of the Safety Data Sheet have to be considered.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

No transport as bulk according IBC - Code.

Land and inland navigation transport ADR/RID

Hazard label(s) 2.2

tunnel restriction code C/E

Special provisions 274, 582, 662

Classification code 2A

Marine transport IMDG

EmS: F-C, S-V

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Other regulations (EU)**

Regulation (EU) No 517/2014 on fluorinated greenhouse gases.

Regulation (EU) 2015/2068 establishing, pursuant to Regulation (EU) No 517/2014, the format of labels for

products and equipment containing fluorinated greenhouse gases.

Regulation (EU) 2015/2067 establishing, pursuant to Regulation (EU) No 517/2014, ~ certification ~ as regards stationary refrigeration, air conditioning and heat pump equipment, and ~ containing fluorinated greenhouse gases.

VOC standard**VOC content** >=99 % 20 °C 11218 hPa**15.2. Chemical Safety Assessment**

The protective measures listed in Sections 6, 7 and 8 of the Safety Data Sheet have to be considered.

An exposure scenario is not required.

Chemical safety assessments for substances in this mixture were carried out.

SECTION 16: Other information**Recommended uses and restrictions**

Use in accordance with regulation (EU) No 517/2014 on fluorinated greenhouse gases.

National and local regulations concerning chemicals shall be observed.

Further information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Sources of key data used

For the preparation of this safety data sheet, information from our suppliers as well as data from the "database of registered substances" of the European Chemicals Agency (ECHA) were used.

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.