

## ! SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Name of product**

R 417A (Isceon MO59)

Art-Nr(n): 0062

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses**

**! Remark**

Restricted to professional users.

**Recommended intended purpose(s)**

Refrigerant.

### 1.3. Details of the supplier of the safety data sheet

**Manufacturer/distributor**

S. Zukausko str. 11, Ramuciai, Kaunas district,

LT - 54464, Lithuania

Phone + 370 37 373248

Fax. + 370 37 373198

E-mail: info@brgroup.eu

www.brgroup.eu

### 1.4. Emergency telephone number

**Emergency advice**

The Poison Information Bureau

Siltnamijų str. 29, LT-2043 Vilnius

Phone +370 5 2362052;

Fax. +370 5 236 21 42,

E-mail.: info@tox.lt

## ! SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories

Hazard Statements Classification procedure

Liquef. Gas

H280

**! Hazard statements for physical hazards**

H280 Contains gas under pressure; may explode if heated.

**2.2. Label elements**

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS04

**! Signal word**

Warning

**! Hazard statements for physical hazards**

H280 Contains gas under pressure; may explode if heated.

**Precautionary Statements****! Storage**

P403 Store in a well-ventilated place.

**Hazardous ingredients for labeling**

1,1,1,2-Tetrafluoroethane (R 134a), butane, Pentafluoroethane (R 125)

**Supplemental Hazard information (EU)****! Health properties**

Asphyxiant in high concentrations.

**! Environmental properties**

Contains fluorinated greenhouse gases.

**! Special rules for supplemental label elements for certain mixtures**

Withdrawal out of the liquid phase only.

**2.3. Other hazards****Adverse human health effects and symptoms**

Contact with liquid may cause cold burns/frostbite.

The inhalation of gas / vapour in high concentrations may cause cardiac arrhythmia.

Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

**Information pertaining to special dangers for human and environment**

Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

Receptacle under pressure.

**! Results of PBT and vPvB assessment**

The substances in this mixture do not meet the PBT/vPvB criteria of REACH, annex XIII.

**! SECTION 3: Composition/ information on ingredients****3.1. Substances**

not applicable

**3.2. Mixtures**

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
811-97-2	212-377-0	1,1,1,2-Tetrafluoroethane (R 134a)	49 - 51	Liq. Gas, H280
354-33-6	206-557-8	Pentafluoroethane (R 125)	45,5 - 47,7	Liq. Gas, H280
106-97-8	203-448-7	n-Butan	3 - 3,5	Flam. Gas 1, H220 / Liq. Gas, H280

**REACH**

CAS No	Name	REACH registration number
811-97-2	1,1,1,2-Tetrafluoroethane (R 134a)	01-2119459374-33
354-33-6	Pentafluoroethane (R 125)	01-2119485636-25
106-97-8	n-Butan	01-2119474691-32

**! Additional advice**

The text of the H-and EUH-phrases is shown in section 16.  
Contains fluorinated greenhouse gases.

**! SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.  
In the event of persistent symptoms receive medical treatment.  
Adhere to personal protective measures when giving first aid.

**! In case of inhalation**

Remove the casualty into fresh air and keep him immobile.  
Seek medical treatment immediately.  
In case of respiratory standstill give artificial respiration by respiratory bag (Ambu bag) or respirator. Send for a doctor.

**! In case of skin contact**

In case of contact with skin wash off with warm water.  
In case of frostbite rinse with plenty of water. Don't remove clothing.  
In case of frostbite spray with lukewarm (not hot) water for at least 15 minutes. Do not remove clothing frozen to the skin. Thaw it with lukewarm water. Apply a sterile dressing. Obtain medical assistance.

**! In case of eye contact**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Call for a doctor immediately.

**In case of ingestion**

Ingestion is not considered a potential route of exposure.

**4.2. Most important symptoms and effects, both acute and delayed****Physician's information / possible symptoms**

The following symptoms may occur in case of strong exposition:

Unconsciousness  
Cardiac arrhythmia (disordered cardiac rhythm).  
Headache  
Nausea  
Confusion  
Dizziness  
Contact with liquid may cause cold burns/frostbite.

**! Physician's information / possible dangers**

Long-term inhaling of separation products may cause pulmonary oedema.

**4.3. Indication of any immediate medical attention and special treatment needed****! Treatment (Advice to doctor)**

Treat symptoms.  
Do not give any preparations of the adrenalin-ephedrine group.

## ! SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### ! Suitable extinguishing media

Product does not burn, fire-extinguishing activities according to surrounding.

Alcohol-resistant foam

Dry powder

Carbon dioxide

Water spray jet

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Carbon monoxide (CO)

Carbon dioxide (CO<sub>2</sub>)

Hydrogen fluoride (HF)

Carbonyl fluoride.

### 5.3. Advice for firefighters

#### Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply ( isolated ).

Wear full protective clothing.

#### ! Additional information

Cool endangered containers with water spray jet.

Exposure to fire may cause containers to rupture / explode.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

## ! SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### ! For non-emergency personnel

Evacuate area.

Keep people away and stay on the upwind side.

#### ! For emergency responders

Remove persons to safety.

Personal protection by wearing close-fitting protective clothing and breathing apparatus.

Pay attention to extension of gas especially at ground (heavier than air) and in direction of the wind.

### 6.2. Environmental precautions

If possible, stop flow of product.

Do not discharge into the drains/surface waters/groundwater.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

If necessary, secure leaky pressure receptacles in a salvage packaging.

Do not discharge into the subsoil/soil.

### 6.3. Methods and material for containment and cleaning up

Ensure adequate air ventilation.

Allow to vaporise.

### 6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

**! SECTION 7: Handling and storage****7.1. Precautions for safe handling****! Advice on safe handling**

Use only in thoroughly ventilated areas.

Transfer and handle only in enclosed systems.

Containers' temperature may not be increased above 50 °C.

Do not heat with open flames.

The working pressure in the receptacle must not exceed the saturation vapour pressure of the pure product resulting at a temperature of 50 °C.

Provide good room ventilation even at ground level (vapours are heavier than air).

Prevent cylinders from falling over.

Avoid release to the environment.

Ensure valve protection device is correctly fitted.

Ensure valve outlet cap nut or plug (where provided) is correctly fitted.

Open valve slowly to avoid pressure shock.

Do not allow backfeed into the container.

Suck back of water into the container must be prevented.

No water to valves, flanges and other fittings.

Purging of pipes and valves with inert gases - to avoid: water, solvents.

**General protective measures**

Do not inhale gases.

**Hygiene measures**

At work do not eat, drink and smoke.

Wash hands before breaks and after work.

**! Advice on protection against fire and explosion**

The product is not flammable in air under ambient conditions of temperature and pressure. When pressurised with air, oxygen or other oxidants, it may become flammable.

Pay attention to general rules of internal fire prevention.

**7.2. Conditions for safe storage, including any incompatibilities****! Requirements for storage rooms and vessels**

Keep in closed original container.

Only use containers that are approved specifically for the substance/product.

Suitable materials: Normalised carbon steel, tempered alloy steel, aluminium alloys, austenitic stainless steels.

Valve: Suitable materials: Brass, copper alloys, carbon steels, aluminium alloys, austenitic stainless steels.

Other material details see ISO 11114.

All regulations and local requirements for the storage of containers have to be respected.

**! Advice on storage compatibility**

Do not store together with combustible materials.

Do not store together with spontaneously flammable materials.

Do not store together with animal feedstuffs.

Do not store together with explosives.

Do not store together with infectious substances.

Do not store together with radioactive material.

Do not store together with toxic liquids or toxic solids.

Do not store together with food.

Do not store together with oxidizing liquids or oxidizing solids.

**! Further information on storage conditions**

Ensure valve protection device is correctly fitted.

Store only in original container at temperature of 50°C maximum (=122°F).

Protect from heat and direct solar radiation.

Prevent cylinders from falling over.

Keep container in a well-ventilated place

### 7.3. Specific end use(s)

#### ! Recommendation(s) for intended use

Use in accordance with regulation (EU) No 517/2014 on fluorinated greenhouse gases.

**! SECTION 8: Exposure controls/personal protection**
**8.1. Control parameters**
**! Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
106-97-8	Butane	WEL, 8 hours Short-term	1450 1810	600 750	EH40, United Kingdom
811-97-2	1,1,1,2-Tetrafluoroethane (HFC 134a)	WEL, 8 hours	4240	1000	EH40, United Kingdom
106-97-8	n-Butane	REL, 8 hours	1900	800	NIOSH, USA

**DNEL-/PNEC-values**
**DNEL worker**

CAS No	Substance name	Value	Code	Remark
354-33-6	Pentafluoroethane (R 125)	16444 mg/m3	DNEL long-term inhalative (systemic)	Assessment factor 7,5, repeated dose toxicity.
811-97-2	1,1,1,2-Tetrafluoroethane (R 134a)	13936 mg/m3	DNEL long-term inhalative (systemic)	Assessment factor 7,5, repeated dose toxicity.

**DNEL Consumer**

CAS No	Substance name	Value	Code	Remark
354-33-6	Pentafluoroethane (R 125)	1753 mg/m3	DNEL long-term inhalative (systemic)	Assessment factor 25, repeated dose toxicity.
811-97-2	1,1,1,2-Tetrafluoroethane (R 134a)	2476 mg/m3	DNEL long-term inhalative (systemic)	Assessment factor 15, repeated dose toxicity.

**PNEC**

CAS No	Substance name	Value	Code	Remark
354-33-6	Pentafluoroethane (R 125)	0,1 mg/l	PNEC aquatic, freshwater	Assessment factor 1000, assessment factor.
		0,6 mg/kg dw	PNEC sediment, freshwater	
		1 mg/l	PNEC aquatic, intermittent release	Assessment factor 100, assessment factor.
811-97-2	1,1,1,2-Tetrafluoroethane (R 134a)	0,75 mg/kg dw	PNEC sediment, freshwater	Extrapolation
		1 mg/l	PNEC aquatic, intermittent release	Assessment factor 100, assessment factor.
		73 mg/l	PNEC sewage treatment plant (STP)	Assessment factor 10, assessment factor.
		0,1 mg/l	PNEC aquatic, freshwater	Assessment factor 1000, assessment factor.
		0,01 mg/l	PNEC aquatic, marine water	Assessment factor 10000

**8.2. Exposure controls****Respiratory protection**

Breathing apparatus in the event of high concentrations.

Keep self contained breathing apparatus readily available for emergency use.

Do not use any filter apparatus.

Respiratory protection complying with EN 137.

In case of rescue and maintenance activities in storage containers use environment-independent breathing apparatus because of risk of suffocation by edging out of air oxygen

**! Hand protection**

Leather gloves

Safety gloves according EN 388

**! Eye protection**

Protective goggles according to EN 166, in case of increased risk add protective face shield.

**! Other protection measures**

Safety shoes with steel toe.

Body covering work clothing, or chemical resistant suit at increased risk.

**Appropriate engineering controls**

Transfer and handle only in enclosed systems.

**! SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties****Appearance**

Gaseous / liquefied under pressure.

**Colour**

colourless

**Odour**

ethereal

**Odour threshold**

not determined

**Important health, safety and environmental information**

	Value	Temperature	at	Method	Remark
<b>pH value</b>	not applicable				
<b>boiling point</b>	-39,1 °C				
<b>not determined</b>	not determined				
<b>Flash point</b>	not applicable				
<b>Vapourisation rate</b>	not determined				
<b>Flammable (solid)</b>	not applicable				
<b>Flammability (gas)</b>	no				
<b>Ignition temperature</b>	not determined				



	Value	Temperature	at	Method	Remark
<b>Self ignition temperature</b>	not determined				
<b>Lower explosion limit</b>	no			ASTM E-681	
<b>Upper explosion limit</b>	no			ASTM E-681	
<b>Vapour pressure</b>	9835 hPa	25 °C			
<b>Relative density</b>	47,57 kg/m <sup>3</sup>	25 °C			
<b>Vapour density</b>	3,8				air = 1
<b>Solubility in water</b>	not determined				
<b>Solubility/other</b>	not determined				
<b>Partition coefficient n-octanol/water (log P O/W)</b>	not determined				
<b>Decomposition temperature</b>	not determined				
<b>Viscosity</b>	not applicable				

**Oxidising properties**

no

**Explosive properties**

no

**9.2. Other information**

Vapours are heavier than air.

**! SECTION 10: Stability and reactivity****10.1. Reactivity**

See section "Possibility of hazardous reactions".

**10.2. Chemical stability**

Stable under recommended conditions of use and storage (see section 7).

**10.3. Possibility of hazardous reactions**

May react violently with oxidants.

When pressurised with air, oxygen or other oxidants, the mixture may become flammable.

Reactions with alkali metals.

Reactions with earth alkali metals.

Reactions with metals in powder form.

Reactions with metal salts in powder form.

Reactions with alkalies.

**10.4. Conditions to avoid**

Heat sources / heat - risk of bursting.

Avoid contact with open flames, glowing metal surfaces, etc..

**10.5. Incompatible materials****! Substances to avoid**

Alkali (lye)

Metals in powder form.

Metallic salts in powder form.

Strong oxidizing agents.

Alkali metals.

Earth alkali metals.

**10.6. Hazardous decomposition products**

Carbon monoxide and carbon dioxide.

Fluorophosgene on contact open flame or glowing objects

Hydrogen fluoride

Carbonyl fluoride

**Thermal decomposition**

Remark No decomposition if used as directed.

**! SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
<b>LD50 acute oral</b>	Study technically not feasible.			
<b>LD50 acute dermal</b>	Study technically not feasible.			
<b>LC50 acute inhalation</b>	> 567000 ppm (4 h)	rat	OECD 403	R-134a
<b>Skin irritation</b>	non-irritant	Guinea pig		R-134a
<b>Eye irritation</b>	non-irritant	rabbit eye		R-134a
<b>Skin sensitization</b>	non-sensitizing	Guinea pig		R-134a
<b>Sensitization respiratory system</b>	non-sensitizing			

**Subacute Toxicity - Carcinogenicity**

	Value	Species	Method	Validation
<b>Subchronic Toxicity</b>	NOAEC 50000 ppm (2 a) Inhalation 6 h/d, 5 d/w	Rat (male / female)	OECD 453	R-134a
<b>Mutagenicity</b>				No experimental information on genotoxicity in vitro and in vivo available.
<b>Reproduction-Toxicity</b>				No indications of toxic effects were observed in reproduction studies in animals.
<b>Carcinogenicity</b>				No indications of carcinogenic effects are available from long-term trials.

**! Specific target organ toxicity (single exposure)**

Substance or mixture is not classified in GHS-criteria as specific target organ toxic with single exposure.

**! Specific target organ toxicity (repeated exposure)**

Substance or mixture is not classified in GHS-criteria as specific target organ toxic with repeated exposure.

**! Aspiration hazard**

not applicable

**Experiences made from practice**

Inhalation causes disordered cardiac rhythm.

Inhalation causes shortness of breath.

Gases have a suffocating effect.

Inhalation causes narcotic effect/intoxication.

**Additional information**

The product has not been tested. The information is derived from the properties of the individual components.

**! SECTION 12: Ecological information****12.1. Toxicity****Ecotoxicological effects**

	Value	Species	Method	Validation
<b>Fish</b>	LC50 450 mg/l (96 h)	Oncorhynchus mykiss	EU Method C.1	R-134a
<b>Daphnia</b>	EC50 980 mg/l (48 h)	Daphnia magna	EU Method C.2	R-134a
<b>Algae</b>	EC50 > 118 mg/l (72 h)	Algae	EU Method C.3	The product has not been tested. The information was derived from products of similar structure or composition.
<b>Bacteria</b>	EC10 > 730 mg/l (6 h)	Pseudomonas putida		R-134a

**12.2. Persistence and degradability**

	Elimination rate	Method of analysis	Method	Validation
<b>Biological degradability</b>	3 % (28 d)		OECD 301 D	Not readily degradable (R-134a).

**12.3. Bioaccumulative potential**

No high bioaccumulation potential.

**12.4. Mobility in soil**

Because of its high volatility, it is unlikely that the product soil, water caused.

**12.5. Results of PBT and vPvB assessment**

The substances in this mixture do not meet the PBT/vPvB criteria of REACH, annex XIII.

**12.6. Other adverse effects**

ODP: 0

GWP: 2346

**! General regulation**

Use in accordance with regulation (EU) No 517/2014 on fluorinated greenhouse gases.

The product has not been tested. The data are derived from the individual components of the mixture.

Avoid release to the environment.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Waste code No.**

14 06 01\*

**Name of waste**

chlorofluorocarbons, HCFC, HFC

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

**Recommendations for the product**

Dispose of as hazardous waste.

Return to manufacturer.

**Recommendations for packaging**

Transportable pressure equipment (empty, residual pressure): Return to supplier / manufacturer.

**General information**

Operators of stationary equipment shall be responsible for putting in place arrangements for the proper recovery.

**! SECTION 14: Transport information**

	ADR/RID	IMDG	IATA-DGR
<b>14.1. UN number</b>	1078	1078	1078
<b>14.2. UN proper shipping name</b>	REFRIGERANT GAS, N.O. S. (50% 1,1,1,2-Tetrafluorethan; 46,6% Pentafluorethan; 3,4% Butan)	REFRIGERANT GAS, N.O.S. (50% 1,1,1,2-Tetrafluoroethane; 46,6% Pentafluoroethane; 3,4% Butane)	Refrigerant gas, n.o.s. (50% 1,1,1,2-Tetrafluoroethane; 46, 6% Pentafluoroethane; 3, 4% Butane)
<b>14.3. Transport hazard class(es)</b>	2.2	2.2	2.2

	ADR/RID	IMDG	IATA-DGR
<b>14.4. Packing group</b>	-	-	-
<b>14.5. Environmental hazards</b>	No	No	No

**14.6. Special precautions for user**

The protective measures listed in Sections 6, 7 and 8 of the Safety Data Sheet have to be considered.

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

not applicable

No transport as bulk according IBC - Code.

**Land and inland navigation transport ADR/RID**

Hazard label(s) 2.2

tunnel restriction code C/E

Special provisions 274, 582, 662

Classification code 2A

**Marine transport IMDG**

EmS: F-C, S-V

**! SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****! Other regulations (EU)**

Regulation (EU) No 517/2014 on fluorinated greenhouse gases.

Regulation (EU) 2015/2068 establishing, pursuant to Regulation (EU) No 517/2014, the format of labels for products and equipment containing fluorinated greenhouse gases.

Regulation (EU) 2015/2067 establishing, pursuant to Regulation (EU) No 517/2014, ~ certification ~ as regards stationary refrigeration, air conditioning and heat pump equipment, and ~ containing fluorinated greenhouse gases.

**VOC standard**

**VOC content** >=99 % 25 °C 9835 hPa

**15.2. Chemical Safety Assessment**

The protective measures listed in Sections 6, 7 and 8 of the Safety Data Sheet have to be considered.

An exposure scenario is not required.

Chemical safety assessments for substances in this mixture were carried out.

**! SECTION 16: Other information****! Recommended uses and restrictions**

Use in accordance with regulation (EU) No 517/2014 on fluorinated greenhouse gases.

National and local regulations concerning chemicals shall be observed.

**Further information**

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 9.2

**! Sources of key data used**

For the preparation of this safety data sheet, information from our suppliers as well as data from the "database of registered substances" of the European Chemicals Agency (ECHA) were used.

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.