

Printed: 22.02.2016

Revision: 18.02.2016 Version 1.4

R449A

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Name of product R 449A

Art-Nr(n).: 0092

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### **Identified uses**

#### Sector of uses [SU]

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen) SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

#### Recommended intended purpose(s)

Refrigerant.

#### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer/distributor

S. Zukausko str. 11, Ramuciai, Kaunas district,

LT - 54464, Lithuania Phone + 370 37 373248 Fax. + 370 37 373198 E-mail: info@brgroup.eu

www.brgroup.eu

#### 1.4. Emergency telephone number Emergency advice

The Poison Information Bureau Siltnamiu str. 29, LT-2043 Vilnius

Phone +370 5 2362052; Fax. +370 5 236 21 42, E-mail.: info@tox.lt

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard

categories

Hazard Statements Classification procedure

Liquef. Gas H280

#### Hazard statements for physical hazards

H280 Contains gas under pressure; may explode if heated.

#### 2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]





Printed: 22.02.2016

Revision: 18.02.2016 Version 1.4

**R449A** 

Signal word Warning

Hazard statements for physical hazards

H280 Contains gas under pressure; may explode if heated.

**Precautionary Statements** 

Storage

P403 Store in a well-ventilated place.

#### Hazardous ingredients for labeling

1,1,1,2-Tetrafluoroethane (R 134a), 2,3,3,3-Tetrafluorprop-1-ene (R 1234yf), Difluoromethane (R 32), Pentafluoroethane (R 125)

#### Supplemental Hazard information (EU)

#### **Health properties**

Asphyxiant in high concentrations.

#### **Environmental properties**

Contains fluorinated greenhouse gases.

#### Special rules for supplemental label elements for certain mixtures

Withdrawal out of the liquid phase only.

#### 2.3. Other hazards

#### Adverse human health effects and symptoms

Contact with liquid may cause cold burns/frostbite.

The inhalation of gas / vapour in high concentrations may cause cardiac arrhythmia.

Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

#### Information pertaining to special dangers for human and environment

Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

#### Results of PBT and vPvB assessment

The substances in this mixture do not meet the PBT/vPvB criteria of REACH, annex XIII.

#### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

not applicable

#### 3.2. Mixtures

#### Hazardous ingredients

| CAS No   | EC No         | Name                                     | [%<br>weight] | Classification according to Regulation (EC) No 1272/2008 [CLP/GHS] |
|----------|---------------|--|---------------|--|
| 811-97-2 | 212-377-0     | 1,1,1,2-Tetrafluoroethane (R 134a)       | 25,7          | Liq. Gas, H280   |
| 354-33-6 | 206-557-8     | Pentafluoroethane (R 125)                | 24,7          | Liq. Gas, H280   |
| 75-10-5  | 200-839-4     | Difluoromethane (R 32)                   | 24,3          | Flam.Gas1, H220 / Liq.Gas, H280                                    |
| 754-12-1 | 468-710-7     | 2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf) | 25,3          | Flam. Gas 1, H220 / Liq. Gas, H280                                 |
| REACH    |               |  |               |  |
| CAS No   | Name          |  |               | <b>REACH</b> registration number                                   |
| 811-97-2 | 1,1,1,2-Tetra | afluoroethane (R 134a)                   |               | 01-2119459374-33   |
| 354-33-6 | Pentafluoro   | ethane (R 125)                           |               | 01-2119485636-25   |
| 75-10-5  | Difluorometh  | nane (R 32)                              |               | 01-2119471312-47   |
| 754-12-1 | 2,3,3,3-Tetra | afluoroprop-1-ene (R 1234yf)             |               | 01-0000019665-61   |



Printed: 22.02.2016

Revision: 18.02.2016 Version 1.4

**R449A** 0092

#### **Additional advice**

The text of the H-phrases is shown in section 16.

Contains fluorinated greenhouse gases.

#### **!SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **General information**

Remove contaminated soaked clothing immediately.

Adhere to personal protective measures when giving first aid.

Seek medical advice immediately.

#### In case of inhalation

Remove the casualty into fresh air and keep him immobile.

Seek medical treatment immediately.

In case of respiratory standstill give artifical respiration by respiratory bag (Ambu bag) or respirator. Send for a doctor.

#### In case of skin contact

In case of contact with skin wash off with warm water.

In case of frostbite rinse with plenty of water. Don't remove clothing.

In case of frostbite spray with lukewarm (not hot) water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.

#### In case of eye contact

Rinse cautiously with water for several minuts. Remove contact lenses, if present and easy to do. Continue rinsing. Call for a doctor immediately.

#### In case of ingestion

Ingestion is not considered a potential route of exposure.

#### 4.2. Most important symptoms and effects, both acute and delayed

#### ! Physician's information / possible symptoms

The following symptoms may occur in case of strong exposition:

Cardiac arrhythmia (disordered cardiac rhythm).

Headache

Nausea

Dizziness

Contact with liquid may cause cold burns/frostbite.

#### Physician's information / possible dangers

Long-term inhaling of separation products may cause pulmonary oedema.

### 4.3. Indication of any immediate medical attention and special treatment needed Treatment (Advice to doctor)

Treat symptoms.

Do not give any preparations of the adrenalin-ephedrine group.

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

Product does not burn, fire-extinguishing activities according to surrounding.

#### Unsuitable extinguishing media

Full water jet



Printed: 22.02.2016

Revision: 18.02.2016 Version 1.4

R449A

#### 5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Formation of explosive gas mixtures in air.

Carbon monoxide (CO)

Hydrogen fluoride (HF)

Carbonyl fluoride.

#### 5.3. Advice for firefighters

#### Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply ( isolated ).

Wear full protective clothing.

#### **Additional information**

Cool endangered containers with water spray jet.

Exposure to fire may cause containers to rupture / explode.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

See chapter 8.

Evacuate area.

#### For emergency responders

Remove persons to safety.

Personal protection by wearing close-fitting protective clothing and breathing apparatus.

Keep people away and stay on the upwind side.

#### 6.2. Environmental precautions

If possible, stop flow of product.

Do not discharge into the drains/surface waters/groundwater.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Do not discharge into the subsoil/soil.

#### 6.3. Methods and material for containment and cleaning up

Ensure adequate air ventilation.

Allow to vaporise.

#### 6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

#### **!SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

Use only in thoroughly ventilated areas.

Transfer and handle only in enclosed systems.

Containers' temperature may not be increased above 50 °C.

Do not heat with open flames.

The working pressure in the receptacle must not exceed the saturation vapour pressure of the pure product resulting at a temperature of 50 °C.

Provide good room ventilation even at ground level (vapours are heavier than air).

Prevent cylinders from falling over.

Avoid release to the environment.

Ensure valve protection device is correctly fitted.



Printed: 22.02.2016

Revision: 18.02.2016 Version 1.4

R449A

Ensure valve outlet cap nut or plug (where provided) is correctly fitted.

Open valve slowly to avoid pressure shock.

Do not allow backfeed into the container.

Suck back of water into the container must be prevented.

No water to valves, flanges and other fittings.

Purging of pipes and valves with inert gases - to avoid: water, solvents.

#### General protective measures

Do not inhale gases/vapours/aerosols.

#### Hygiene measures

At work do not eat, drink and smoke.

#### Advice on protection against fire and explosion

The product is not flammable in air under ambient conditions of temperature and pressure. When pressurised with air, oxygen or other oxidants, it may become flammable.

Pay attention to general rules of internal fire prevention.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep in closed original container.

Ventilate store-rooms thoroughly.

Use transportable pressure equipment.

Suitable materials: Normalised steel and carbon steel, tempered steel, aluminium alloys, stainless steel.

Valve: Suitable materials: Brass, copper alloys, carbon steels, aluminium alloys, stainless steel.

#### ! Advice on storage compatibility

Do not store with spontaneously flammable materials.

Do not store together with combustible liquids or combustible solids.

Do not store together with animal feedstuffs.

Do not store together with explosives.

Do not store together with infectious substances.

Do not store together with radioactive material.

Do not store together with toxic liquids or toxic solids.

Do not store together with food.

Do not store together with oxidizing liquids or oxidizing solids.

#### Further information on storage conditions

Store closed container at cool and aired place.

Store only in original container at temperature of 50°C maximum (=122°F).

Prevent cylinders from falling over.

Protect of heat.

#### 7.3. Specific end use(s)

#### Recommendation(s) for intended use

See section 1.2

Use in accordance with regulation (EU) No 517/2014 on fluorinated greenhouse gases.

#### **!SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### Ingredients with occupational exposure limits to be monitored

| CAS No   | Name                                    | Code         | [mg/m3] | [ppm] | Remark                     |
|----------|---|--------------|---------|-------|----------------------------|
| 811-97-2 | 1,1,1,2-Tetrafluoroethane (HFC<br>134a) | WEL, 8 hours | 4240    | 1000  | EH40,<br>United<br>Kingdom |

# BRGroup

Safety Data Sheet according to Regulation (EC)
No. 1907/2006 (REACH)

Printed: 22.02.2016

Revision: 18.02.2016 Version 1.4

R449A

0092

#### **DNEL-/PNEC-values DNEL** worker

| CAS No     | Substance name                             | Value              | Code                                 | Remark                                |
|------------|--|--------------------|--------------------------------------|---------------------------------------|
| 354-33-6   | Pentafluoroethane (R 125)                  | 16444<br>mg/m3     | DNEL long-term inhalative (systemic) | Assessment factor 7,5                 |
| 75-10-5    | Difluoromethane (R 32)                     | 7035 mg/<br>m3     | DNEL long-term inhalative (systemic) | Assessment factor 7,5, Extrapolation  |
| 754-12-1   | 2,3,3,3-Tetrafluorprop-1-ene (R 1234yf)    | 23000<br>mg/m3     | DNEL long-term inhalative (systemic) | Assessment factor 5, Extrapolation    |
| 811-97-2   | 1,1,1,2-Tetrafluoroethane (R<br>134a)      | 13936<br>mg/m3     | DNEL long-term inhalative (systemic) | Assessment factor 7,5                 |
| DNEL Consu | umer                                       |                    |                                      |                                       |
| CAS No     | Substance name                             | Value              | Code                                 | Remark                                |
| 354-33-6   | Pentafluoroethane (R 125)                  | 1753 mg/<br>m3     | DNEL long-term inhalative (systemic) | Assessment factor 25                  |
| 75-10-5    | Difluoromethane (R 32)                     | 750 mg/m3          | DNEL long-term inhalative (systemic) | Assessment factor 25                  |
| 754-12-1   | 2,3,3,3-Tetrafluorprop-1-ene (R<br>1234yf) | 186400<br>mg/m3    | DNEL long-term inhalative (systemic) | Assessment factor 5, Extrapolation    |
| 811-97-2   | 1,1,1,2-Tetrafluoroethane (R<br>134a)      | 2476 mg/<br>m3     | DNEL long-term inhalative (systemic) | Assessment factor 15                  |
| PNEC       |  |                    |                                      |                                       |
| CAS No     | Substance name                             | Value              | Code                                 | Remark                                |
| 354-33-6   | Pentafluoroethane (R 125)                  | 0,6 mg/kg<br>dw    | PNEC sediment, freshwater            | Extrapolation                         |
|            |  | 1 mg/l             | PNEC aquatic, intermittent release   | Assessment factor 100, Extrapolation  |
|            |  | 0,1 mg/l           | PNEC aquatic, freshwater             | Assessment factor 1000, Extrapolation |
| 75-10-5    | Difluoromethane (R 32)                     | 0,142 mg/l         | PNEC aquatic, freshwater             | Assessment factor 1000                |
|            |  | 1,42 mg/l          | PNEC aquatic, intermittent release   | Assessment factor 100                 |
|            |  | 0,534 mg/<br>kg dw | PNEC sediment, freshwater            | Extrapolation                         |
| 754-12-1   | 2,3,3,3-Tetrafluorprop-1-ene (R 1234yf)    | 0,25 mg/l          | PNEC aquatic, freshwater             | Assessment factor 10, Extrapolation   |
|            |  | 0,025 mg/l         | PNEC aquatic, marine water           | Assessment factor 100, Extrapolation  |
|            |  | 0,33 mg/l          | PNEC aquatic, intermittent release   | Assessment factor 100, Extrapolation  |
|            |  | 1,35 mg/<br>kg dw  | PNEC sediment, freshwater            | Extrapolation                         |
|            |  | 0,135 mg/<br>kg dw | PNEC sediment, marine water          | Extrapolation                         |



Printed: 22.02.2016

Revision: 18.02.2016 Version 1.4

**R449A** 

#### **DNEL-/PNEC-values (continued)**

| CAS No   | Substance name                        | Value             | Code                               | Remark  |
|----------|---------------------------------------|-------------------|------------------------------------|---|
|          |                                       | 0,72 mg/<br>kg dw | PNEC soil                          | Calculation method does not exist                               |
|          |                                       | 0,1 mg/l          | PNEC aquatic, freshwater           | Assessment factor<br>1000, Calculation<br>method does not exist |
|          |                                       | 1 mg/l            | PNEC aquatic, intermittent release | Assessment factor 100,<br>Calculation method<br>does not exist  |
| 811-97-2 | 1,1,1,2-Tetrafluoroethane (R<br>134a) | 0,1 mg/l          | PNEC aquatic, freshwater           | Assessment factor 1000, Extrapolation                           |
|          |                                       | 0,01 mg/l         | PNEC aquatic, marine water         | Assessment factor 10000, Extrapolation                          |
|          |                                       | 1 mg/l            | PNEC aquatic, intermittent release | Assessment factor 100, Extrapolation                            |
|          |                                       | 73 mg/l           | PNEC sewage treatment plant (STP)  | Assessment factor 10, Extrapolation                             |

#### 8.2. Exposure controls

#### **Respiratory protection**

Breathing apparatus in the event of high concentrations.

Keep self contained breathing apparatus readily available for emergency use.

Respiratory protection complying with EN 137.

In case of rescue and maintenance activities in storage containers use environment-independent breathing apparatus because of risk of suffocation by edging out of air oxygen

#### ! Hand protection

Low-temperature-resistant gloves

Leather gloves

Protective gloves complying with EN 374.

#### Eye protection

safety goggles, in case of increased risk add protective face shield Safety goggles with side protection complying with EN 166.

#### Other protection measures

Safety shoes with steel toe.

Body covering work clothing, or chemical resistant suit at increased risk.

#### ! Limitation and surveillance of the environment

See chapter 7.

#### Appropriate engineering controls

Transfer and handle only in enclosed systems.

#### **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties Appearance Gaseous / liquefied under pressure. Colour colourless ethereal

# BRGroup

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) Printed: 22.02.2016
Revision: 18.02.2016 Version 1.4
R449A
0092

#### **Odour threshold**

not determined

#### Important health, safety and environmental information

|                           | Value                | Temperature | at                | Method         | Remark  |
|---------------------------|----------------------|-------------|-------------------|----------------|---|
| pH value                  | not<br>applicable    |             |                   |                |   |
| boiling point             | -46 °C               |             | 1013 hPa          |                |   |
| melting point             | not determined       |             |                   |                |   |
| Flash point               | not<br>applicable    |             |                   |                |   |
| Vapourisation rate        | not determined       |             |                   |                |   |
| Flammable (solid)         | not<br>applicable    |             |                   |                |   |
| Flammability (gas)        |                      |             |                   |                | The mixture does not meet the criteria for classification as a flammable gas. |
| Ignition temperature      | not<br>applicable    |             |                   |                |   |
| Self ignition temperature | not<br>applicable    |             |                   |                |   |
| Lower explosion limit     | no                   |             |                   |                |   |
| Upper explosion limit     | no                   |             |                   |                |   |
| Vapour pressure           | 12748 hPa            | 25 °C       |                   |                |   |
| Relative density          | 1,1 g/cm3            | 25 °C       |                   |                | information<br>concerns to<br>liquid phase                                    |
| Bulk density              |                      |             |                   | not applicable |   |
| Vapour density            | 3,07                 | 25 °C       | 1013 hPa          |                | air = 1   |
| Solubility in water       | No data<br>available |             |                   |                |   |
| Solubility/other          |                      |             | not<br>determined |                |   |



Printed: 22.02.2016

Revision: 18.02.2016 Version 1.4

**R449A** 0092

|                          | Value   | Temperature | at | Method | Remark |
|--------------------------|---------|-------------|----|--------|--------|
| Partition coefficient n- | No data |             |    |        |        |

octanol/water (log P O/W)

ino data available

Decomposition temperature

not applicable

Viscosity not determined not determined

**Oxidising properties** 

no

**Explosive properties** 

no

9.2. Other information

Vapours are heavier than air.

#### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

See section "Possibility of hazardous reactions".

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

When pressurised with air, oxygen or other oxidants, the mixture may become flammable.

#### 10.4. Conditions to avoid

Heat sources / heat - risk of bursting.

Avoid contact with open flames, glowing metal surfaces, etc..

#### 10.5. Incompatible materials

#### Substances to avoid

Metals in powder form.

Metallic salts in powder form.

Strong oxidizing agents.

Alkali metals.

Earth alkali metals.

#### 10.6. Hazardous decomposition products

Carbon monoxide

Fluorophosgene on contact open flame or glowing objects

Hydrogen fluoride

#### Thermal decomposition

Remark No decomposition if used as directed.



Printed: 22.02.2016 Revision: 18.02.2016 Version 1.4

R449A 0092

#### **!SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

#### Acute toxicity/Irritation/Sensitization

|  | Value/Validation                             | Species            | Method | Remark  |
|--|--|--------------------|--------|---|
| LD50 acute oral                                  | not applicable                               |                    |        |   |
| LD50 acute dermal                                | not applicable                               |                    |        |   |
| LC50 acute inhalation                            | > 405000 ppm (4 h)                           | rat                |        | R-1234yf  |
| Skin irritation                                  | low irritant effect - not necessary to label | rabbit             |        | R-134a  |
| Eye irritation                                   | low irritant - no<br>labeling duty           | rabbit eye         |        | R-134a  |
| Skin sensitization                               | non-sensitizing                              | Laboratory animals |        | R-134a  |
| Sensitization respiratory system                 | non-sensitizing                              | Laboratory animals |        | R-134a  |
| Subacute Toxicity - C                            | arcinogenicity                               |                    |        |   |
| •  |  |                    |        |   |
|  | Value  | Species            | Method | Validation  |
| Subchronic Toxicity                              |  | Species<br>Rat     | Method | No effects of toxicological   |
|  | Value  |                    | Method |   |
|  | Value  NOAEL 233 mg/l  Inhalation            |                    | Method | No effects of toxicological   |
| Subchronic Toxicity                              | Value  NOAEL 233 mg/l  Inhalation            |                    | Method | No effects of toxicological significance.  No experimental information on genotoxicity in vivo  |
| Subchronic Toxicity  Mutagenicity  Reproduction- | Value  NOAEL 233 mg/l  Inhalation            |                    | Method | No effects of toxicological significance.  No experimental information on genotoxicity in vivo available.  No indications of toxic effects were observed in reproduction studies in |

No data available

Specific target organ toxicity (repeated exposure)

No data available

**Aspiration hazard** 

not applicable



Printed: 22.02.2016

Revision: 18.02.2016 Version 1.4

**R449A** 

#### ! Toxicity test (Additional information)

No indication of cancerogenic effects at humans available.

#### Experiences made from practice

May cause frostbite.

Gases have a suffocating effect.

Inhalation causes narcotic effect/intoxication.

#### Additional information

The product has not been tested. The information is derived from the properties of the individual components.

#### **!SECTION 12: Ecological information**

#### 12.1. Toxicity

#### **Ecotoxicological effects**

|                                     | Value             | •                |       | Species                | Method     |   | Validation                       |
|-------------------------------------|-------------------|------------------|-------|------------------------|------------|---|----------------------------------|
| Fish                                | LC50              | 450 mg/l (96 h)  |       | Oncorhynchus<br>mykiss |            |   | R-134a                           |
| <b>Daphnia</b> EC50 980 mg/l (48 h) |                   | Daphnia magna    |       |                        | R-134a     |   |                                  |
| Algae                               | gae EC50 142 mg/l |                  | Algae |                        |            |   | R-32                             |
| 12.2. Persisten                     | ce and            | degradability    |       |                        |            |   |                                  |
|                                     |                   | Elimination rate | Metho | od of analysis         | Method     | , | Validation                       |
| Physico-chemi<br>degradability      | ical              | not determined   |       |                        |            |   |                                  |
| Biological degradability            |                   | 3 % (28 d)       |       |                        | OECD 301 D |   | Not readily degradable (R-134a). |

#### 12.3. Bioaccumulative potential

Bioaccumulation improbable.

#### 12.4. Mobility in soil

not determined

Adsorption in the soil is not likely.

#### 12.5. Results of PBT and vPvB assessment

The substances in this mixture do not meet the PBT/vPvB criteria of REACH, annex XIII.

#### 12.6. Other adverse effects

ODP: 0 GWP: 1397

#### **General regulation**

Use in accordance with regulation (EU) No 517/2014 on fluorinated greenhouse gases.

Avoid release to the environment.

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste code No.

Name of waste

14 06 01\*

chlorofluorocarbons, HCFC, HFC

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.



Printed: 22.02.2016

Revision: 18.02.2016 Version 1.4

**R449A** 

#### Recommendations for the product

Dispose of as hazardous waste.

Return to manufacturer.

#### Recommendations for packaging

Transportable pressure equipment (empty, residual pressure): Return to supplier / manufacturer.

#### **General information**

Operators of stationary equipment shall be responsible for putting in place arrangements for the proper recovery.

#### **SECTION 14: Transport information**

|                                  | ADR/RID   | IMDG   | IATA-DGR  |
|----------------------------------|---|--|---|
| 14.1. UN number                  | 1078  | 1078   | 1078  |
| 14.2. UN proper shipping name    | REFRIGERANT GAS, N.O. S. (1,1,1,2-Tetrafluorethan, Pentafluorethan) | REFRIGERANT GAS, N.O.S. (1,1,1,2-Tetrafluoroethane, Pentafluoroethane) | Refrigerant gas, n.o.s. (1, 1,1,2-Tetrafluoroethane, Pentafluoroethane) |
| 14.3. Transport hazard class(es) | 2.2   | 2.2  | 2.2   |
| 14.4. Packing group              | -   | -  | -   |
| 14.5. Environmental hazards      | No  | No   | No  |

#### 14.6. Special precautions for user

The protective measures listed in Sections 6, 7 and 8 of the Safety Data Sheet have to be considered.

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

No transport as bulk according IBC - Code.

#### Land and inland navigation transport ADR/RID

Hazard label(s) 2.2 tunnel restriction code C/E Classification code 2A

#### **!SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture ! Other regulations (EU)

Regulation (EU) No 517/2014 on fluorinated greenhouse gases.

Regulation (EU) 2015/2068 establishing, pursuant to Regulation (EU) No 517/2014, the format of labels for products and equipment containing fluorinated greenhouse gases.

Regulation (EU) 2015/2067 establishing, pursuant to Regulation (EU) No 517/2014, ... certification ... as regards stationary refrigeration, air conditioning and heat pump equipment, and refrigeration units of refrigerated trucks ... containg f-gases ....

#### ! VOC standard

**VOC content** >=99 % 25 ℃12748 hPa

#### 15.2. Chemical Safety Assessment

The protective measures listed in Sections 6, 7 and 8 of the Safety Data Sheet have to be considered. Chemical safety assessments for substances in this mixture were carried out.



Printed: 22.02.2016 Revision: 18.02.2016 Version 1.4

R449A

#### **!SECTION 16: Other information**

#### Recommended uses and restrictions

Use in accordance with regulation (EU) No 517/2014 on fluorinated greenhouse gases.

National and local regulations concerning chemicals shall be observed.

#### **Further information**

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 1.3

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.